

FEATURES

- KF25 Flange Connector
- Low Maintenance Zirconium Cell
- 0-1000ppm Oxygen Sensor
- Operates in a Vacuum, 20 Torr
- 3 Year Warranty
- 2 Alarm Relays
- 24V DC Power Supply Included (99097)
- International Power Supply Included (99141)
- No Drift Due to Environmental or Temperature Changes
- UL, CE Approval

Why choose PureAire?

PureAire Monitoring Systems, Inc. is an industry leader in oxygen monitoring, analyzers, and gas detection. For over 25 years, we have dedicated ourselves to the safety of our clients, and the customers they serve, by manufacturing monitors that are long-lasting, accurate, and reliable. PureAire takes pride in providing exceptional customer service, along with 24/7 availability to our technical service department.

Why a KF25 0-1000ppm Trace Oxygen Analyzer?

The PureAire KF25 0-1000ppm O₂ Analyzer is designed for continuous monitoring where inert gases are used to create an environment where there is little to no oxygen present, such as glove boxes and vacuum chambers.

What gases can be detected with a KF25 0-1000ppm Trace Oxygen Analyzer?

PureAire's KF25 0-1000ppm O₂ Analyzer can be used in process chambers where inert gases, including nitrogen, argon, and carbon dioxide are used.

Easy to Use

Secure the analyzer to the wall so that the display is visible. The oxygen sensor and KF25 flange can be installed directly into the glove box, process or vacuum chamber, up to 10 feet from the analyzer. Connect the analyzer to a 24V DC 250mA power source. After a brief startup period, the analyzer will begin measuring oxygen levels. Oxygen levels will be displayed clearly on the screen, for easy access and visibility.

***Not recommended for use in environments over 1000ppm**

Trace Oxygen Analyzer, KF25 0-1000ppm

ITEM#99097-Includes Domestic Power Supply

ITEM#:99119-Incl 30' Remote Cable, Domestic Pwr Supply

ITEM#: 99141-Includes International Power Supply

Product Summary

PureAire's KF25 0-1000ppm Trace Oxygen Analyzer is ideal for facilities requiring continuous monitoring of 3D printers, glove boxes, nitrogen gas lines, vacuum chambers, as well as any locations where there is little to no oxygen present. The unit's sensor mounts directly into the process chamber with the use of a KF type vacuum fitting. The analyzer is well suited for semiconductor tools, OLED manufacturers, 3D printing and, for any industry applications where inert gases including, but not limited to, nitrogen, helium, and argon are used in a vacuum. PureAire's stable, long-life zirconium oxide sensor will last many years in maintained environments without needing to be replaced.

Facilities That Need This Product

- *Semiconductor Tools*
- *OLED Manufacturers*
- *3D Printers*
- *Direct Metal Laser Sintering and DMP Printers*
- *Inert Vacuum Environments*

Top Advantages of Oxygen Deficiency Monitor





Oxygen Deficiency Alarm

PureAire's O2 Monitor comes with 2 adjustable alarm relay setpoints that can connect to a horn/strobe, exhaust fan, 8 channel controller, remote display, or into building systems.


Easy To Use



The Air Check O2 Deficiency Monitor provides constant monitoring with little to no adjustments, saving you time and money while allowing the monitor to operate seamlessly. Our quality sensor makes this the longest lasting O2 monitor on the market.




Top Accessories




**8 Channel Touch Screen
Programmable Controller**

ITEM #: 99233



Remote Digital Display

ITEM #: 99187



Red Horn/Strobe

ITEM #: 42002



1-888-788-8050

info@pureaire.net
pureairemonitoring.com

1140 Ensell Road
Lake Zurich, IL 60047
1-847-726-6000