

SENSIT[®] GOLD 2

MULTI GAS DETECTOR

FIELD-PROVEN GAS SAFETY

LOCATE ABOVE & BELOW GROUND LEAKS



Readings in
PPM, LEL,
and/or
%VOL

Methane &
Propane
Selectable

Audible/Visual
Alarms & Tick
Mode

Configurable
Up To 4 Gases

Replaceable
Alkaline
Batteries



METHANE GAS CONVERSION

% GAS	% LEL	PPM	% GAS	% LEL	PPM
-	0.1	50	2.0	40.0	20,000
-	0.2	100	2.5	50.0	25,000
-	1.0	500	3.0	60.0	30,000
0.1	2.0	1,000	3.5	70.0	35,000
0.5	10.0	5,000	4.0	80.0	40,000
1.0	20.0	10,000	4.5	90.0	45,000
1.5	30.0	15,000	5.0	100.0	50,000

ALARM PRESET THRESHOLDS

Combustible Gas Alarm	Preset for 50% LEL
Carbon Monoxide (CO)	Preset at 35 PPM
Oxygen (O2)	Preset at Below 19.5% & Above 23.5%
Hydrogen Sulfide (H2S)	Preset at 10 PPM
Hydrogen Cyanide (HCN)	Preset to PPM



LEL/PPM SENSOR

INFRARED COMMUNICATIONS

- | Download Calibration Data
- | Communicate with Smart-Cal

3 BUTTON OPERATION

A

B

C

Power On/Off	Tick Control	Data Save
Mute	Barhole	Manually Zero Sensors
Smart-Cal Features	Test Modes	Change Menu Items
Exit Menu	Select Menu Items	

Learn more at gasleaksensors.com