

SENSIT[®] GOLD 3

MULTI GAS DETECTOR

WORKER & COMMUNITY SAFETY

LOCATE ABOVE & BELOW GROUND LEAKS



GPS &
Datalogging

Rechargeable
Battery

Flashlight
Feature

Rubberized
Housing

Two Speed
Pump

**FAST
DETECTION
TO AS LITTLE
AS 5 PPM!**



METHANE GAS CONVERSION

% GAS	% LEL	PPM	% GAS	% LEL	PPM
-	0.1	50	2.0	40.0	20,000
-	0.2	100	2.5	50.0	25,000
-	1.0	500	3.0	60.0	30,000
0.1	2.0	1,000	3.5	70.0	35,000
0.5	10.0	5,000	4.0	80.0	40,000
1.0	20.0	10,000	4.5	90.0	45,000
1.5	30.0	15,000	5.0	100.0	50,000

LED DOME ALARM COLORS

COLOR	INDICATION
Solid Green	Ready
Flashing Green	Low Battery Indication
Solid Yellow	Low Condition For Combustible Gas (5% - 9.9% LEL)
Solid Red	Potentially Hazardous for Combustible Gas (10 to 49.9% LEL)
Flashing Red +Audible Alarm	Alarm Condition, Sensor Failure Or Flow Block >50% LEL Combustible Gas CO - 35 PPM, H2S - 10PPM, O2 - <19.5% or > 23.5%
Solid Blue	Busy, User In Menus, Calibration, Smart-link 360 Viewing Logs



FLASHLIGHT

LEL/PPM SENSOR

TICK WHEEL

3 BUTTON OPERATION

A	B	C
Power On/Off	Access Menu for Tick	Save Data
Mute	Barhole	Autozero
Activate Smart-Cal	Leak Search	Scroll Through Menu Items
Escape Menu	Purge	Activate Flashlight
	Other Special Modes	

Learn more at gasleaksensors.com